

STATUS 160 BASE



SATIN CA WHITE SAGE / GUNMETAL



SATIN SMOKE / ARCTIC BLUE

The Status 160 may be an all-new bike, but it's really an all-new way of thinking about how to have the most fun possible on two wheels

- Focused on fun and featuring our Mixed-Wheel Trail Geometry, the Status frameset is a few frills, all thrills FSR delivery system crafted from our hard-charging and hard-wearing M5 alloy and is designed not only to take a hit, but keep asking for more.
- Fox's FLOAT 36 Rhythm calls their venerable Grip damper into service in the name of adventurous riders everywhere, offering impressively controlled travel with plenty of trail-feel that puts confidence on speed dial. The two-position Sweep adjustment ensures the FLOAT 36 Rhythm is right at home dealing out its 160-millimeters of travel in just about any environment while 36-millimeter stanchions promise plenty of stiffness for precise handling at the limit.
- Quality suspension unlocks some serious free speed, so to slow it all down, we tasked SRAM's proven Code R brakes with stopping duties. Forged four-piston calipers offer serious stopping power, while 200-millimeter rotors on both ends of the bike promise plenty of fade-free bite when it matters.

STATUS 160 BASE	S1	S2	S3	S4	S5
B-B Drop (mm)	8.5	8.5	8.5	8.5	8.5
Head-Tube Length (mm)	95	100	110	120	130
B-B Height (mm)	347	347	347	347	347
B-B Drop (low BB) (mm)	17.5	17.5	17.5	17.5	17.5
Chain-Stay Length (mm)	426	426	426	426	426
Seat-Tube Length (mm)	400	400	420	440	465
Head-Tube Angle (low BB) (degrees)	63.2	63.2	63.2	63.2	63.2
Fork Rake/Offset (mm)	44	44	44	44	44
B-B Height (low BB) (mm)	338	338	338	338	338
Head-Tube Angle (degrees)	63.7	63.7	63.7	63.7	63.7
Trail (low BB) (mm)	141	141	141	141	141
Fork Length (full) (mm)	567	567	567	567	567
Reach (low BB) (mm)	417	437	462	487	512
Front-Center (low BB) (mm)	756	778	808	837	867
Seat-Tube Angle (degrees)	76	76	76	76	76
Stack (low BB) (mm)	610	614	623	632	641
Wheelbase (mm)	1181	1203	1233	1264	1292
Crank Length (mm)	170	170	170	170	170
Handlebar Width (mm)	800	800	800	800	800
Stem Length (mm)	40	40	40	40	40
Saddle Width (mm)	143	143	143	143	143
Seatpost Length (mm)	125	170	170	170	150

SPECS	Specifications subject to change without notice.
FRAME	M5 alloy chassis and rear-end, Mixed wheel Trail Geometry, threaded BB, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 160mm of travel
SEAT BINDER	Alloy, 38.6mm
FORK	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, 160mm of travel
REAR SHOCK	FOX FLOAT X Performance, Rx Trail Tune, EVOL Air sleeve, 2-position lever w/ LSR adjustment, 230x60mm
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm width
STEM	Alloy Trail Stem, 35mm bar bore
GRIPS	Deity, Knuckleduster, Black
SADDLE	Body Geometry Bridge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9mm, S1:125, S2: 150mm, S3/S4/S5: 170mm
FRONT BRAKE	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
REAR BRAKE	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
CHAIN	SRAM NX Eagle, 12-speed
CRANKSET	SRAM NX Eagle, DUB, 170mm
CHAINRINGS	32T
BOTTOM BRACKET	SRAM DUB, BSA 73mm, Threaded
REAR DERAILLEUR	SRAM NX Eagle, 12-speed
SHIFT LEVERS	SRAM NX Eagle, trigger, 12-speed
CASSETTE	SRAM NX Eagle, 12-speed, 11-50t
RIMS	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
FRONT HUB	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
REAR HUB	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry
FRONT TIRE	
REAR TIRE	
INNER TUBES	Standard, Presta Valve

PART NO.	DESCRIPTION	COLOR	SIZE
93722-7201	STATUS 160 WHTSGE/GUN S1	SATIN CA WHITE SAGE / GUNMETAL	S1
93722-7202			S2
93722-7203			S3
93722-7204			S4
93722-7205			S5
93722-7301	STATUS 160 SMK/ARCTBLU S1	SATIN SMOKE / ARCTIC BLUE	S1
93722-7304			S4
93722-7302			S2
93722-7303			S3
93722-7305			S5